

JATMA国内自主規制グレーディング用試験データ提出

申請会社 プリチストーンジャパン株式会社

商品名 REGNO GR-XII

提出日 平成30年11月22日

扁平率	代表サイズ	LI/SS	転がり抵抗係数(RRC)	グレーディング	ウェットグリップ性能(G)	グレーディング
70's	175 70 R 14	84S	8.0	A	140	b
	195 65 R 15	91H	7.4	AA	145	b
65's	175 65 R 14	82H	8.4	A		
	205 65 R 15	94H	7.5	A		
60's	215 60 R 16	95V	7.5	AA		
	175 60 R 16	82H	7.5	A		
55's	195 60 R 15	88H	7.7	A		
	215 55 R 16	93V	7.5	AA		
50's	185 55 R 15	82V	8.0	A		
	195 55 R 16	87V	7.9	A		
45's	235 50 R 17	96V	7.5	AA	141	b
	215 50 R 17	95V XL	7.2	AA		
40's	205 50 R 17	89V	8.1	A		
	245 45 R 17	95W	7.4	AA		
35's	225 45 R 18	95W XL	7.4	AA		
	215 45 R 18	89W	8.2	A		
30's	215 45 R 17	91W XL	7.6	A		
	245 40 R 20	95W	7.4	AA		
25's	255 40 R 18	95W	7.1	AA		
	245 40 R 19	98W XL	7.5	AA		
20's	225 40 R 18	88W	8.4	A		
	245 35 R 20	95W XL	7.4	AA		
15's	255 35 R 18	90W	8.2	A		
	235 35 R 19	91W XL	8.0	A		
10's	275 30 R 19	96W XL	7.9	A		

単位 N/kN		単位 (%)	
転がり抵抗係数 (RRC)	等級	ウェットグリップ性能 (G)	等級
RRC ≤ 6.5	AAA	155 ≤ G	a
6.6 ≤ RRC ≤ 7.7	AA	140 ≤ G ≤ 154	b
7.8 ≤ RRC ≤ 9.0	A	125 ≤ G ≤ 139	c
9.1 ≤ RRC ≤ 10.5	B	110 ≤ G ≤ 124	d
10.6 ≤ RRC ≤ 12.0	C		

扁平率	サイズ	LI/SS	RRC	ウェット
70's	175 70 R 14	84S	A	b
	180 70 R 14	88H	A	
65's	175 65 R 14	82H	A	
	175 65 R 15	84H	A	
	185 65 R 14	86H	A	
	185 65 R 15	88H	A	
	205 65 R 15	94H	AA	
	205 65 R 16	95H	AA	
60's	195 65 R 15	91H	AA	
	215 60 R 16	95V	AA	
	215 60 R 16	95V	AA	
	225 60 R 16	98V	AA	
	185 55 R 15	82V	A	
	185 55 R 16	83V	A	
55's	195 55 R 16	87V	A	
	205 55 R 16	91V	AA	
	215 55 R 16	93V	AA	
	215 55 R 17	94V	AA	
	225 55 R 16	95V	AA	
	225 55 R 17	97W	AA	
50's	225 55 R 18	98V	AA	
	235 55 R 17	99W	AA	

扁平率	サイズ	LI/SS	RRC	ウェット
50's	205 50 R 17	89V	A	b
	225 50 R 16	92V	A	
	225 50 R 18	95W	AA	
	235 50 R 17	96V	AA	
	245 50 R 18	100W	AA	
	215 50 R 17	95V XL	AA	
45's	225 50 R 17	98V XL	A	
	235 50 R 18	101V XL	A	
	215 45 R 18	89W	A	
	225 45 R 17	91W	A	
	235 45 R 17	94W	AA	
	235 45 R 18	94W	AA	
40's	215 45 R 17	91W XL	AA	
	245 45 R 17	95W	AA	
	245 45 R 19	98W	AA	
	255 45 R 18	99W	AA	
	225 45 R 18	95W XL	AA	
	225 45 R 19	96W XL	AA	
35's	245 45 R 18	100W XL	AA	
	255 45 R 19	104W XL	AA	

扁平率	サイズ	LI/SS	RRC	ウェット
40's	225 40 R 18	88W	A	b
	225 40 R 19	89W	A	
	235 40 R 18	91W	AA	
	235 40 R 19	92W	AA	
	245 40 R 17	91W	AA	
	245 40 R 18	93W	AA	
35's	245 40 R 20	95W	AA	
	255 40 R 18	95W	AA	
	275 40 R 19	101W	AA	
	245 40 R 19	98W XL	AA	
	255 40 R 19	100W XI	AA	
	265 40 R 20	104W XL	AA	
30's	255 35 R 18	90W	A	
	265 35 R 18	93W	A	
	265 35 R 19	94W	A	
	235 35 R 19	91W XL	AA	
	245 35 R 19	93W XL	AA	
	245 35 R 20	95W XL	AA	
25's	275 35 R 19	100W XL	AA	
	275 35 R 20	102W XL	AA	
20's	275 30 R 19	96WXL	A	
	275 30 R 20	97W XL	A	