

### JATMA国内自主規制グレーディング用試験データ提出

申請会社 **横浜ゴム株**

商品名 **BluEarth-Es ES32**

提出日 **令和5年10月30日**

扁平率	代表サイズ	LI/SS	転がり抵抗係数(RRC)	グレーディング
80's	135 80 R 12	68S	8.6	A
70's	145 70 R 12	69S	8.3	A
	145 65 R 13	69S	8.2	A
65's	195 65 R 15	91S	7.4	AA
	215 65 R 15	96S	7.2	AA
60's	165 60 R 14	75T	8.8	A
	225 60 R 17	99H	7.1	AA
55's	155 55 R 14	69V	8.5	A
	225 55 R 18	98V	6.9	AA
50's	165 50 R 15	73V	8.8	A
	235 50 R 18	95V	7.1	AA
45's	205 45 R 16	83V	9.0	A
	225 45 R 18	96W XL	7.4	AA
40's	205 40 R 17	84V XL	8.7	A
35's	225 35 R 19	84W	7.8	A

ウェットグリップ性能	グレーディング
131	c
143	b

単位 (N/kN)		単位 (%)	
転がり抵抗係数 (RRC)	等級	ウェットグリップ性能 (G)	等級
RRC ≤ 6.5	AAA	155 ≤ G	a
6.6 ≤ RRC ≤ 7.7	AA	140 ≤ G ≤ 154	b
7.8 ≤ RRC ≤ 9.0	A	125 ≤ G ≤ 139	c
9.1 ≤ RRC ≤ 10.5	B	110 ≤ G ≤ 124	d
10.6 ≤ RRC ≤ 12.0	C		

扁平率	サイズ	LI/SS	RRC	ウェット
80's	135 80 R 12	68S	A	c
	145 80 R 12	74S		
	145 80 R 13	75S		
	155 80 R 13	79S		
	165 80 R 13	83S		
	175 80 R 14	88S		
70's	145 70 R 12	69S	A	c
	155 70 R 12	73S		
	155 70 R 13	75S		
	165 70 R 13	79S		
	165 70 R 14	81S		
	175 70 R 13	82T		
	175 70 R 14	84S		
	185 70 R 13	86S		
	185 70 R 14	88S		
	195 70 R 14	91H		
215 70 R 15	98S			
65's	145 65 R 13	69S	A	c
	145 65 R 15	72H		
	155 65 R 13	73S		
	155 65 R 14	75S		
	165 65 R 13	77S		
	165 65 R 14	79S		
	165 65 R 15	81S		
	175 65 R 14	82S		

扁平率	サイズ	LI/SS	RRC	ウェット
65's	175 65 R 15	84S	A	c
	185 65 R 14	86T		
	185 65 R 15	88S		
	195 65 R 14	89H		
	195 65 R 15	91S	AA	b
	195 65 R 16	92V	A	
	205 65 R 15	94H	A	
	205 65 R 16	95H	AA	
	215 65 R 15	96S	A	
	215 65 R 16	98H	A	
60's	165 60 R 14	75T	A	c
	165 60 R 15	77H		
	175 60 R 14	79H		
	175 60 R 15	81H		
	175 60 R 16	82H		
	185 60 R 14	82H		
	185 60 R 15	84H		
	185 60 R 16	86H		
	195 60 R 15	88H		
	195 60 R 16	89H		
	195 60 R 17	90H		
	205 60 R 15	91H		
	205 60 R 16	92H		
215 60 R 16	95H			
215 60 R 17	96H			
225 60 R 17	99H	AA	b	

扁平率	サイズ	LI/SS	RRC	ウェット		
55's	155 55 R 14	69V	A	c		
	165 55 R 14	72V				
	165 55 R 15	75V				
	175 55 R 15	77V				
	185 55 R 15	82V				
	185 55 R 16	83V				
	195 55 R 15	85V				
	195 55 R 16	87V				
	205 55 R 15	88V				
	205 55 R 16	91V				
50's	215 55 R 16	93H	A	b		
	215 55 R 17	94V				
	225 55 R 17	97W				
	225 55 R 18	98V			AA	
	165 50 R 15	73V			A	c
	165 50 R 16	75V				
	215 50 R 17	91V				
	195 50 R 15	82V				
	195 50 R 16	84V				
	205 50 R 16	87V				
205 50 R 17	89V					
215 50 R 17	95V XL					
225 50 R 16	92V					
225 50 R 17	94V					
235 50 R 18	97W	AA				

扁平率	サイズ	LI/SS	RRC	ウェット
45's	205 45 R 16	83V	A	b
	215 45 R 17	91V XL		
	225 45 R 17	91V		
	215 45 R 18	93W XL		
	225 45 R 17	94V XL		
	235 45 R 17	97V XL		
40's	225 45 R 18	95W XL	A	b
	205 40 R 17	84V XL		
	215 40 R 17	87V XL		
	215 40 R 18	85W		
	225 40 R 18	92W XL		
	235 40 R 18	95W XL		
	245 40 R 18	93W		
35's	245 40 R 19	94W	A	b
	225 35 R 19	84W		
	255 35 R 18	90W		
	265 35 R 18	93W		